



Product Information

The Luminetworx™ PoE Line of warehouse lighting high bays. This innovative PoE fixture is available in three different configurations, a one foot, two foot and four-foot model. Each add on increases the lumen out output by 5100 lumens for a maximum output of 20400 lumens. All aluminum construction allows for a long-lasting high-quality fixture. All Luminetworx™ PoE fixtures are certified and rated for indoor use.

Product Specifications

Vendor Item Number	LVES-1F5250-HB LVES-2F10500-HB LVES-4F21000-HB
LED Chip	SMD 3030
CCT	6000K
Luminous Efficacy	170 LM/W
Lumens	5100 / 10200 / 20400
Wattage	30 / 60 / 120
Beam Angle	90°
Power Factor	>0.95
Dimming	10-100
Product Family	Luminetworx
Finish	Aluminum
Lens	Frosted
CRI	80
Beam Angle	90°
IP Rating / IC Rated	IP20 / Yes
Design Use	Indoor
Length	1 – 4 feet
Sensor	Auto dimming / on/off
Lighting Control	Luminetworx

Product Information

Certifications	ETL, CE
Warranty	Five Years
Lifecycle	50,000 Hours
Connection Type	PoE
Driver Type	PoE LED
Units Per Assembly	1 / 2 / 4 pcs
Fixture Weight	1.5 – 6 kgs

LV Energy Systems |

304 South Jones Boulevard
Las Vegas, NV 89107



Installation

