



Product Information

The Luminetworx™ PoE Line of warehouse lighting high bays. This innovative PoE fixture is available in three different configurations, a one foot, two foot and four-foot model. Each add on increases the lumen out output by 5100 lumens for a maximum output of 20400 lumens. All aluminum construction allows for a long-lasting high-quality fixture. All Luminetworx™ PoE fixtures are certified and rated for indoor use.

Product Specifications

Vendor Item Number	LVES-F2408U-G
LED Chip	SMD 4014
CCT	1000K
Luminous Efficacy	N/A
Lumens	100
Wattage	5
Beam Angle	N/A
Power Factor	>0.95
Dimming	N/A
Product Family	Luminetworx
Finish	White
Lens	Frosted
CRI	N/A
Housing Material	ABS
IP Rating	IP20
Design Use	Indoor
Dimensions	347.5 x 232 x 42 mm
Sensor	N/A
Lighting Control	Luminetworx

Product Information

Certifications	UL924, ROHS		
Warranty	Two Years	Housing Material	ABS
Lifecycle	20,000 Hours	IP Rating	IP20
Connection Type	PoE	Design Use	Indoor
Driver Type	PoE LED	Dimensions	347.5 x 232 x 42 mm
Units Per Assembly	1 pc	Sensor	N/A
Fixture Weight	.95kgs	Lighting Control	Luminetworx



LV Energy Systems |
 304 South Jones Boulevard
 Las Vegas, NV 89107

